



# PJ-20H



## Product Description

4 square inch electrical junction box for use with nonmetallic sheathed cable

**Brand:** flexBOX®  
**Catalog #:** PJ-20H

**Height:** 4 in.  
**Width:** 4 in.  
**Depth:** 1-5/8 in.  
**Volume:** 20.5 cu. in.  
**Type of Installation:** New Work  
**Wall Box**

**Carton Quantity:** 48  
**Carton Weight:** 15 lb.

**UPC:** 085339990000  
**UNSPSC:** 39121332  
**Patents:**  
U.S. Patent No. 6,365,831 B1  
**Country of Origin:** United States of America

## FEATURES

Machine tapped cover screw holes, cover screws included

## APPLICATION

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications - 2 HR fire resistive walls

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)  
*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

## COLOR

Black

## ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

## MATERIAL

Polyvinyl Chloride

Plated carbon steel fasteners

## MOUNTING

Stud mount hanger bracket offset for flush mount plaster ring