

# Sealing Cover

## For GUA Outlet Boxes

### Type GUASC

#### Use:

Converts ½", ¾" and 1" trade size Type GUA malleable iron outlet boxes into 25% fill sealing fittings.

#### Features:

- Removable plug for pouring sealing compound.
- O-Ring gasket provided to assure watertightness.
- Can be used with O-Z/Gedney EYC sealing compound.

#### Material/Finish:

Malleable Iron/Zinc Electroplated  
Steel Set Screws  
Buna-N O-Ring

#### Optional Finish:

Hot Dip or Mechanical Galvanized.  
Add suffix "G" to standard catalog number.  
Contact your local representative for pricing and availability.

#### Third Party Certification:



UL Listed: E-97032  
Class I, Div. 1, 2, Groups C, D  
Class I, Zone 1, 2, Groups IIA, IIB  
Class II, Div. 1, 2, Groups E, F, G  
Class III  
Suitable for wet locations



CSA Certified: LR20945

#### Applicable Third Party Standards:

UL Standard: 886  
CSA Standard: C22.2 No. 30  
NEC Articles 500-503 & 505  
Mil. Spec: Mil-F-28675  
Fed. Spec: A-A-50563

#### Suggested Specifications:

Where accessory covers for hazardous location outlet boxes are required for sealing, increasing volume or mounting pendant lighting fixtures, they shall be malleable iron construction and UL Listed. These accessory covers shall be O-Z/Gedney Type GUASC, GUATE, GUADC, GUAFC or GUAHC.

#### Note:

**1** GUASC-1 is suitable for use with ½", ¾" and 1" trade size Type GUA malleable iron outlet boxes only. See page BA18.

**2** Splices and taps not allowed in sealing fittings per NEC Article 501.

Catalog Number	Turning Radius "R"	Maximum Body Height "A"
GUASC-1	2½"	1¾"

