

MODELS 510 & 511 ROOM-TO-ROOM FANS



Easily installs in interior walls to move heated or cooled air from one room to another. Spreads heat from fireplaces, cool air from air conditioners to adjoining rooms.

FEATURES

GRILLE:

- Two contemporary styled grilles complement modern
- White polymeric grilles can be painted to match any decor

- Permanently lubricated, thermally protected, plug-in
- Motor assembly offers fast, easy "twist-lock" installation
- Solid state speed control for fan speed and sound level selection

HOUSING:

- Requires 11-5/8" square hole through both interior walls
- Housing can be fastened to walls in serveral ways allows flexibility to meet almost any mounting situation
- Adjustable housing fits walls from 3" to 51/2" thick
- Housing 25 gage finished with rugged black electricallybonded epoxy paint

SPECIFICATIONS

MODEL	VOLTS	AMPS	RPM	SONES	CFM
510	120	1.7	1550	6.5	380
511	120	0.9	1575	4.5	180



based on laboratory measurements.



TYPICAL SPECIFICATION


Ventilator shall be Broan Model 510 (Model 511).

Ventilator shall be installed in an interior wall 3" to 5½" thick NOT through a fire-rated wall.

Ventilator shall be steel housing finished with electricallybonded epoxy paint. Grille to be white polymeric.

Motor assembly shall be removable and permanently lubricated. RPM shall not exceed 1550 (Model 510), 1575 (Model 511).

Air delivery shall be no less than 380 CFM and sound level no greater than 6.5 Sones (Model 510), 180 CFM and 4.5 Sones (Model 511). All air and sound ratings shall be certified by HVI. Units shall be U.L. listed.





REFERENCE	QTY.	REMARKS	Project		
			Location		
			Architect		
			Engineer		
			Contractor		
			Submitted by Date		