

CEILING MOUNT - 900, 1500 CFM

Single, impact resistant centrifugal blower wheel driven by low RPM motor. Housing dimensions: 22" x 18" x 18" (55.9 cm x 45.7 cm x 45.7 cm). Sturdy, low profile metal grille finished with white enamel paint (23 7/8" x 19 7/8") (60.6 cm x 50.4 cm). Discharges horizontally or vertically through 8" x 12" (20.3 cm x 30.5 cm) duct connector. AMCA certified.



Part No.	Description	CFM (Horiz. / Vert.) @ 0.1"SP	Sones (Horiz. / Vert.) @ 0.1"SP	Duct	Weight (lb.)	UPC
L900	Ceiling mount 120 VAC, white enamel steel grille	905 / 892	4.0 / 3.4	8" x 12"	64.2	026715124572
L1500	Ceiling mount 120 VAC, white enamel steel grille	1526 / 1519	8.4 / 8.4	8" x 12"	64.3	026715124589

IN-LINE - 100, 150, 200, 250, 300 CFM

Single, impact resistant centrifugal blower wheel driven by low RPM motor. Housing dimensions: 12 1/4" x 12 1/4" x 11 3/4" (31.1 cm x 31.1 cm x 29.8 cm). In-line models have removable access panel and do not include insulation. AMCA certified.



Part No.	Description	CFM (Horiz. / Vert.) @ 0.1"SP	Sones (Horiz. / Vert.) @ 0.1"SP	Duct	Weight (lb.)	UPC
L100L	In-line, 120 VAC	108 / 98	0.7 / 0.8	6"	22.9	026715124596
L150L	In-line, 120 VAC	148 / 138	1.0 / 1.4	6"	22.9	026715124602
L200L	In-line, 120 VAC	196 / 177	1.9 / 1.6	8"	19.8	026715124619
L250L	In-line, 120 VAC	245 / 224	2.3 / 2.5	8"	19.8	026715124626
L300L	In-line, 120 VAC	294 / 261	3.0 / 3.7	8"	19.9	026715124633

IN-LINE - 400, 500, 700 CFM

Two, impact resistant centrifugal blower wheels driven by low RPM motor. Housing dimensions: 21 1/2" x 12 1/4" x 11 3/4" (54.6 cm x 31.1 cm x 29.8 cm). Two 4 1/2" x 18 1/2" (11.4 cm x 47 cm) duct connectors. In-line models have removable access panel and do not include insulation. AMCA certified.



Part No.	Description	CFM (Horiz. / Vert.) @ 0.1"SP	Sones (Horiz. / Vert.) @ 0.1"SP	Duct	Weight (lb.)	UPC
L400L	In-line, 120 VAC	415 / 415	1.6 / 1.7	4 1/2" x 18 1/2"	33.9	026715124640
L400KL	In-line, 120 VAC, suitable for kitchen installation	385 / 391	2.7 / 2.4	4 1/2" x 18 1/2"	36.3	026715125128
L500L	In-line, 120 VAC	526 / 516	2.4 / 3.8	4 1/2" x 18 1/2"	33.9	026715124657
L500KL	In-line, 120 VAC, suitable for kitchen installation	476 / 482	3.7 / 4.1	7 3/4" x 33 3/4"	36.3	026715125135
L700L	In-line, 120 VAC	686 / 667	3.8 / 5.0	4 1/2" x 18 1/2"	34.0	026715124664