




Industrial grade 15A locking devices

Product description


2-pole, 2-wire non-grounding
15A, 125V/AC
NEMA L1-15



7546



7540



CWL115FI



CWL115FO

Industrial grade plugs & connectors

Rating	A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
15	125	L1-15	Straight body	0.31-0.47" (7.9-11.9mm)	BK	□ 7546	—	•	
			Straight body	0.30-0.56" (7.5-14.3mm)	BK	—	□ 7506	•	

Industrial grade receptacles

Rating	A	V/AC	NEMA	Description	Color	Single receptacle	Duplex receptacle	
15	125	L1-15	Standard industrial		BK	□ CWL115R	—	• •
			Standard industrial		BK	—	□ 7540	•

Industrial grade flanged inlets & outlets

Rating	A	V/AC	NEMA	Description	Color	Flanged inlet	Flanged outlet	
15	125	L1-15	Standard industrial		BK & W	□ CWL115FI	□ CWL115FO ¹¹	• •

¹¹Only UL Listed

Accessories for NEMA L1-15 locking devices

Description	Catalog no.	
Diecast aluminum single receptacle cover, vertical mount, for FS/FD Boxes	□ 7420	• •
Glass-filled nylon flanged inlet/outlet cover, vertical mount, for 15A devices	□ WP1	• •



7420



WP1

Dimensional information:
C-79, C-80

Plug & connector specification information:
NEMA L1-15: C-85

Receptacle specification information:
NEMA L1-15: C-87

Flanged inlet & flanged outlet specification information:
NEMA L1-15: C-88

Color information:

BK (Black), W (White)



(Black)

(White)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32