




WARM TILES®

FLOOR WARMING CABLES




EasyHeat's Warm Tiles® floor-warming system is easily installed on subfloor or concrete slab, in thin-set or self-leveling compound materials. Warm Tiles cables, which are supplied with standard 10-foot cold leads, are designed to supply at least 12 watts per square foot when installed per instructions. Available in 120 and 240 Vac kits, Warm Tiles systems are easy for distributors to stock and sell. Warm Tiles cables are UL Listed, CSA Certified and conform to European directives. Please contact your local EasyHeat representative for layout assistance.



120 AC VOLT

CATALOG NUMBER	PLYWOOD SUBFLOOR*	CONCRETE SUBFLOOR**	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
DFT1011	9-13 ft ²	7-9 ft ²	"Blue" cable kit, 120 Vac	2	7.5	0-13627-01611-8	  
DFT1016	14-18 ft ²	10-13 ft ²	"Red" cable kit, 120 Vac	2	8.0	0-13627-01612-5	
DFT1022	19-26 ft ²	14-19 ft ²	"Green" cable kit, 120 Vac	2	9.0	0-13627-01613-2	
DFT1030	27-34 ft ²	20-26 ft ²	"Yellow" cable kit, 120 Vac	2	9.5	0-13627-01614-9	
DFT1039	35-42 ft ²	27-33 ft ²	"Purple" cable kit, 120 Vac	2	10.0	0-13627-01615-6	
DFT1048	43-54 ft ²	34-39 ft ²	"Orange" cable kit, 120 Vac	2	12.0	0-13627-01616-3	
DFT1059	55-65 ft ²	40-48 ft ²	"Brown" cable kit, 120 Vac	2	13.0	0-13627-01617-0	
DFT1069	66-72 ft ²	48-54 ft ²	"Beige" cable kit, 120 Vac	2	13.0	0-13627-01618-7	
DFT1079	73-82 ft ²	55-62 ft ²	"White" cable kit, 120 Vac	1	7.0	0-13627-01619-4	
DFT1088	83-92 ft ²	63-69 ft ²	"Pink" cable kit, 120 Vac	1	7.5	0-13627-01609-5	
DFT1098	93-102 ft ²	70-76 ft ²	"Silver" cable kit, 120 Vac	1	8.0	0-13627-01608-8	
DFT1108	103-113 ft ²	77-85 ft ²	"Black" cable kit, 120 Vac	1	8.5	0-13627-01607-1	

240 AC VOLT

CATALOG NUMBER	PLYWOOD SUBFLOOR*	CONCRETE SUBFLOOR**	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
DFT2021	18-25 ft ²	13-19 ft ²	"A" cable kit, 240 Vac	2	8.0	0-13627-01621-7	  
DFT2031	26-35 ft ²	20-27 ft ²	"B" cable kit, 240 Vac	2	10.0	0-13627-01622-4	
DFT2053	48-55 ft ²	35-44 ft ²	"C" cable kit, 240 Vac	2	12.0	0-13627-01623-1	
DFT2065	60-70 ft ²	45-54 ft ²	"D" cable kit, 240 Vac	2	15.4	0-13627-01624-8	
DFT2078	71-83 ft ²	55-63 ft ²	"E" cable kit, 240 Vac	2	16.2	0-13627-01625-5	
DFT2095	90-100 ft ²	64-75 ft ²	"F" cable kit, 240 Vac	2	18.7	0-13627-01626-2	
DFT2118	110-130 ft ²	84-94 ft ²	"G" cable kit, 240 Vac	2	21.2	0-13627-01627-9	
DFT2137	131-145 ft ²	95-108 ft ²	"H" cable kit, 240 Vac	2	22.0	0-13627-01628-6	
DFT2157	146-165 ft ²	109-125 ft ²	"I" cable kit, 240 Vac	1	12.0	0-13627-01629-3	
DFT2175	166-184 ft ²	126-138 ft ²	"J" cable kit, 240 Vac	1	12.7	0-13627-01630-9	
DFT2195	185-204 ft ²	139-153 ft ²	"K" cable kit, 240 Vac	1	13.8	0-13627-01631-6	
DFT2215	205-224 ft ²	154-169 ft ²	"L" cable kit, 240 Vac	1	15.1	0-13627-01632-3	

*Use Standard spacing on floors that are located above heated areas.

**Use Alternating spacing on concrete slab floors or in rooms with excessive heat loss such as solariums.