

WARM TILES®


ELECTRIC FLOOR WARMING CABLE FOR UNCOUPLING MEMBRANE




EasyHeat's Warm Tiles Electric Floor Warming Cable for Uncoupling Membrane floor warming electric heating cables are designed to be installed in floors in conjunction with uncoupling membrane systems. This product is intended to gently warm flooring materials such as marble, ceramic, glass and porcelain tile, slate, granite and poured or dimensional stone, in addition to laminate and engineered hardwood products. Warm Tiles Electric Floor Warming Cables greatly enhances the comfort level of these beautiful flooring materials.

Warm Tiles Electric Floor Warming Cable floor warming systems utilize state-of-the-art heating cables, hardware and electrical controls for an economical and long lasting floor warming system. Warm Tiles Electric Floor Warming Cable systems are designed for use inside residential and commercial buildings of standard North American construction. The heating cables can be installed at 2" or 3" spacing depending on the desired wattage output. The warming electric heating cables are CSA Certified for use in both the U.S. and Canada.

120 AC VOLT

CATALOG NUMBER	SUBFLOOR COVERAGE (SQUARE FOOTAGE)			POWER CONSUMPTION (WATTS)	CARTON QTY	CARTON WEIGHT	UPC	CERTIFICATIONS
	PLYWOOD AT 3.6" SPACING ①	CONCRETE AT 2.4" SPACING ②	CABLE LENGTH					
DMC1012	1.11 m ² (12 ft ²)	0.74 m ² (8 ft ²)	13.4 m (44 ft)	159	2	1.0kg (2.1lbs)	0-13627-188105	
DMC1016	1.49 m ² (16 ft ²)	1.02 m ² (11 ft ²)	17.7 m (58 ft)	208	2	1.2kg (2.7lbs)	0-13627-188112	
DMC1021	1.95 m ² (21 ft ²)	1.30 m ² (14 ft ²)	23.2 m (76 ft)	274	2	1.4kg (3.1lbs)	0-13627-188129	
DMC1025	2.32 m ² (25 ft ²)	1.58 m ² (17 ft ²)	26.8 m (88 ft)	315	2	1.5kg (3.4lbs)	0-13627-188136	
DMC1031	2.88 m ² (31 ft ²)	1.95 m ² (21 ft ²)	33.2 m (109 ft)	394	2	1.6kg (3.6lbs)	0-13627-188143	
DMC1042	3.90 m ² (42 ft ²)	2.60 m ² (28 ft ²)	44.2 m (145 ft)	522	2	1.8kg (4.0lbs)	0-13627-188150	
DMC1053	4.92 m ² (53 ft ²)	3.34 m ² (36 ft ²)	56.4 m (185 ft)	665	2	2.1kg (4.6lbs)	0-13627-188167	
DMC1065	6.04 m ² (65 ft ²)	3.99 m ² (43 ft ²)	68.3 m (224 ft)	805	2	2.5kg (5.6lbs)	0-13627-188174	
DMC1081	7.53 m ² (81 ft ²)	5.02 m ² (54 ft ²)	84.4 m (277 ft)	998	2	3.2kg (7.2lbs)	0-13627-188181	
DMC1097	9.01 m ² (97 ft ²)	6.13 m ² (66 ft ²)	101.5 m (333 ft)	1200	2	3.9kg (8.7lbs)	0-13627-188198	
DMC1114	10.59 m ² (114 ft ²)	7.15 m ² (77 ft ²)	119.5 m (392 ft)	1412	3	4.6kg (10.3lbs)	0-13627-188204	

240 AC VOLT

CATALOG NUMBER	SUBFLOOR COVERAGE (SQUARE FOOTAGE)			POWER CONSUMPTION (WATTS)	CARTON QTY	CARTON WEIGHT	UPC	CERTIFICATIONS
	PLYWOOD AT 3.6" SPACING ①	CONCRETE AT 2.4" SPACING ②	CABLE LENGTH					
DMC2021	1.95 m ² (21 ft ²)	1.30 m ² (14 ft ²)	22.9 m (75 ft)	268	2	1.1kg (2.5lbs)	0-13627-188211	
DMC2025	2.32 m ² (25 ft ²)	1.58 m ² (17 ft ²)	26.8 m (88 ft)	317	2	1.4kg (3.0lbs)	0-13627-188228	
DMC2031	2.88 m ² (31 ft ²)	1.95 m ² (21 ft ²)	33.2 m (109 ft)	393	2	1.6kg (3.6lbs)	0-13627-188235	
DMC2042	3.90 m ² (42 ft ²)	2.60 m ² (28 ft ²)	44.2 m (145 ft)	522	2	2.1kg (4.7lbs)	0-13627-188242	
DMC2054	5.02 m ² (54 ft ²)	3.44 m ² (37 ft ²)	57.6 m (189 ft)	679	2	2.8kg (6.2lbs)	0-13627-188259	
DMC2063	5.85 m ² (63 ft ²)	3.90 m ² (42 ft ²)	66.8 m (219 ft)	788	2	3.2kg (7.1lbs)	0-13627-188266	
DMC2081	7.53 m ² (81 ft ²)	5.21 m ² (56 ft ²)	85.3 m (280 ft)	1008	2	4.1kg (9.1lbs)	0-13627-188273	
DMC2097	9.01 m ² (97 ft ²)	6.13 m ² (66 ft ²)	101.5 m (333 ft)	1200	2	4.9kg (10.9lbs)	0-13627-188280	
DMC2113	10.50 m ² (113 ft ²)	7.06 m ² (76 ft ²)	118.6 m (389 ft)	1399	3	5.7kg (12.7lbs)	0-13627-188297	
DMC2131	12.17 m ² (131 ft ²)	8.18 m ² (88 ft ²)	136.2 m (447 ft)	1610	3	6.6kg (14.6lbs)	0-13627-188303	
DMC2163	15.14 m ² (163 ft ²)	10.13 m ² (109 ft ²)	169.2 m (555 ft)	1997	3	7.0kg (15.5lbs)	0-13627-188310	
DMC2196	18.21 m ² (196 ft ²)	12.17 m ² (131 ft ²)	203.3 m (667 ft)	2400	3	7.3kg (16.3lbs)	0-13627-188327	
DMC2231	21.46 m ² (231 ft ²)	14.31 m ² (154 ft ²)	239.0 m (784 ft)	2824	3	8.6kg (19.0lbs)	0-13627-188334	

① 12 watts per square foot

② 18 watts per square foot