



Model SLM700 shown with mounting base options (ordered separately)

► Model SLM700

StreamLine® Modular Electronic Sounder

Model SLM700 is a multifunctional electronic sounder developed with a multiple input technology that is capable of producing two different tones controllable via independent electric contacts.

Model SLM700 offers a high acoustic performance through 2 channels offering 64 tones, 32 tones per input selectable via dip switch.

Model SLM700 body material is a self extinguishing polycarbonate material with high impact and UV resistance suitable for outdoor applications.

FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC*
- PLC compatible with PNP or NPN connections*
- Produces two tones
- Choice of 64 selectable tones
- Adjustable volume between 55 dBa to 95 dBa @10' (65-105 dBa @ 1m)

- Seven mounting base options
- Type 3R, IP65 enclosure
- CE Certified and RoHS Compliant
- UL and cUL listed

*Voltage and PLC connections are dependent on selected base.

MODEL	VOLTAGE	DECIBELS MIN. - MAX.		MAXIMUM OPERATING CURRENT (mA)			
		10'	1M	12VAC/DC	24VAC/DC	120VAC	240VAC
SLM700 *	12-24VAC/DC or 120-240VAC	55-95	65-105	240	280	60	35

*For body color, indicate GY for Gray or R for Red.


Weight (unit(s) + base = total weight)

SLM700	VOLTAGE	SHALLOW BASE	DEEP BASE	WALL MOUNT	PIPE MOUNT	TWIN WALL MOUNT	2-STACK DOCK BASE	3-STACK DOCK BASE
7.76 oz 0.22 kg	12-24VAC/DC	2.12 oz 0.06 kg	4.23 oz 0.12 kg	6.70 oz 0.19 kg	5.29 oz 0.15 kg	9.17oz 0.26 kg	14.46 oz 0.41 kg	21.16 oz 0.60 kg
	120-240 VAC	–	6.0 oz 0.17 kg	8.47 oz 0.24 kg	6.70 oz 0.19 kg	12.35 oz 0.35kg	16.58 oz 0.47 kg	24.69 oz 0.70 kg

StreamLine® Modular Electronic Sounder (SLM700)

SPECIFICATIONS

Operating Temperature: -22°F to 122°F -30°C to 50°C



REPLACEMENT PARTS








Description	Part Number
Light Visor	SLMB23V

HOW TO ORDER

- Specify model number SLM300 and color for Opaque Lens or SLM350 and color for Fresnel Lens
- Specify required mounting base (see chart)
- Optional dome guard
For shallow mounting base (SLMDG1)
For deep mounting base (SLMDG2)
- Accessories for Twin and Wall Mount Bases
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
1" NPT Adapter (SLMNPT1)
1/2" NPT Adapter (SLMNPT2)
- Accessories for Dock Base
Wall Mount Bracket (SLMB23W)
1/2" NPT Adaptor (SLMB23N)
Retaining Ring (SLM-RR)



MOUNTING BASE OPTIONS

Image	Model Number	Base Color	Voltage	Dimensions
 Shallow Base	SLMBS-012-024GY	Gray	12-24VAC/DC	
 Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
	SLMBD-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBD-012-024R	Red	12-24VAC/DC	
	SLMBD-120-240GY	Gray	120-240VAC	
 Wall Mount	SLMBD-120-240R	Red	120-240VAC	
	SLMBW-012-024GY	Gray	12-24VAC/DC	
	SLMBW-PNP-012-024GY	Gray	12-24VAC/DC	
 Pipe Mount	SLMBW-120-240GY	Gray	120-240VAC	
	SLMBP-012-024GY	Gray	12-24VAC/DC	
	SLMBP-PNP-012-024GY	Gray	12-24VAC/DC	
 Twin Wall Mount	SLMBP-120-240GY	Gray	120-240VAC	
	SLMBT-012-024GY	Gray	12-24VAC/DC	
	SLMBT-PNP-012-024GY	Gray	12-24VAC/DC	
 2-Stack Dock Base	SLMBT-120-240GY	Gray	120-240VAC	
	SLMB2-024GY	Gray	24VAC/DC	
 3-Stack Dock Base	SLMB2-120-240GY	Gray	120-240VAC	
	SLMB3-024GY	Gray	24VAC/DC	
	SLMB3-120-240GY	Gray	120-240VAC	