


80045 - F20T12/CW/ECO

GE Cool White Ecolux® T12

Passes TCLP, which can lower disposal costs.



CAUTIONS & WARNINGS

Caution

· Lamp may shatter and cause injury if broken

- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.


Warning

Risk of Electric Shock

- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Rated Life Bulb Material Starting Temperature (MIN) LEED-EB MR Credit Linear Fluorescent - Straight Linear T12 Medium Bi-Pin (G13) 9000.0 hrs Soda lime 10.0 °C 478 picograms Hg per mean lumen hour TCLP compliant Full Wattage

Additional Info Primary Application

PHOTOMETRIC CHARACTERISTICS

Initial Lumens1200.0Mean Lumens1150.0Nominal Initial Lumens per Watt60Color Temperature4100.0 KColor Rendering Index (CRI)60.0

ELECTRICAL CHARACTERISTICS

Wattage Voltage	20.0 57.0
Open Circuit Voltage (rapid start) (MAX)	220.0 V
Open Circuit Voltage (rapid	157 V @ 10 °C
start) Min @ Temperature Cathode Resistance Ratio - Rh/	4.25
Rc (MIN) Cathode Resistance Ratio - Rh/	6.5
Rc (MAX) Open Circuit Voltage	210 V @ 10 °C
(after preheating) Min @	210 V @ 10 0
Temperature Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length 24.0000 in(609.6 mm) (MOL) Minimum Overall Length 23.6700 in(601.2 mm) Nominal Length 24.000 in(609.6 mm) Bulb Diameter (DIA) (MIN) 1.410 in(35.8 mm) 1.590 in(40.4 mm) Bulb Diameter (DIA) (MAX) Bulb Diameter (DIA) 1.500 in(38.1 mm) Max Base Face to Base Face 23.220 in(589.8 mm) (A) Face to End of Opposing Pin 23.400 in(594.4 mm) (B) (MIN) Face to End of Opposing Pin 23.500 in(596.9 mm) (B) (MAX) End of Base Pin to End of 23.670 in(601.2 mm) Opposite Pin End (C)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 80045 F20T12/CW/ECO 2015-1 Case 10043168800454 24 Unit 1 24

043168800457