




GE
Lighting

78950 - FLE15/2/R30/D/CD

GE energy smart® CFL 15 watt R30 floodlight 1-pack

• The GE energy smart® indoor floodlight CFLs feature a GE Spiral® bulb on the inside that uses 75% less energy and lasts up to 5 times longer than incandescent indoor reflectors. These bulbs' funnel shape help direct light where it is needed better than a standard CFL or incandescent bulb. Use GE energy smart® indoor floodlight CFLs in indoor recessed track and recessed fixtures to create broad beams of light in any room or space

- \$55 in energy savings over the life of the bulb based on 3 hours per day usage
- 65 watt replacement uses only 15 watts
- Estimated yearly energy costs \$1.81 based on 3 hours per day \$0.11 per kWh
- Lasts 9.1 years based on 3 hours per day usage
- R30 indoor floodlight with medium base for use in directional fixtures such as recessed can lighting



GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	R30
Base	Medium Screw (E26)
Equivalent Wattage (NOM)	60.0 W
Rated Life (NOM)	10000.0 h
Bulb Material	Soft glass
Total Harmonic Distortion (THD) (NOM)	140.0 %
Primary Application	Indoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	650.0
Mean Lumens (NOM)	520.0
Nominal Initial Lumens per Watt (NOM)	43.33333
Color Temperature (NOM)	6500.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	15.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.300 in(134.6 mm)
Bulb Diameter (DIA) (NOM)	3.750 in(95.2 mm)

PRODUCT INFORMATION

Product Code	78950
Description	FLE15/2/R30/D/CD
Standard Package	Case
Standard Package GTIN	10043168789506
Standard Package Quantity	3
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	3
UPC	043168789509