



GE
Lighting

49767 - GE259MAX-N/ULTRA

GE LFL UltraMax™ Electronic High Efficiency Multivolt Instant Start Ballast

- Energy saving high efficiency instant start electronic ballast (> 90%)
- Multi-Voltage Technology handles voltage from 120 to 277V
- Active Current Regulation regulates the output to each lamp with individual lamp inverter modules.
- Anti-Striation Control for better light quality, with no striations.
- Cold temperature -20F Minimum Starting Temperature



CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Properly ground ballast and fixture.
 - Turn power off before servicing--see instructions.

GENERAL CHARACTERISTICS

Lamp Type	Fluorescent -
Bulb	Electronic
Ballast Type	High Efficiency Multivolt Instant Start
Starting Method	Instant start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Additional Info	Anti-striation control/Auto- restart/Thermally protected

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	50.0 Hz
--------------------------	---------

DIMENSIONS

Weight	1.4 lb
Exit Type	
Remote Mounting Distance	18.0 ft
Remote Mounting Wire Gauge	18.0 AWG

PRODUCT INFORMATION

Product Code	49767
Description	GE259MAX-N/ULTRA
Standard Package	Case
Standard Package GTIN	
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168497671