

86675 - GEM100MLTLA3D-5

GE HID Distributor Replacement Kit Magnetic Metal Halide Core and Coil Ballast

• Magnetic ballast construction ideal for a wide variety of lighting applications.

• Precision-wound aluminum coils, ensuring even heat dissipation and the highest electrical integrity

Distributor replacement kit contains the appropriate core & coil with color coded leads, a properly rated capacitor
and ignitor (if required) and all other components required for ballast replacement

• Quad ballast (120, 208, 240, 277)





CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

- Properly ground ballast and fixture.
- Turn power off before servicing--see instructions.

*GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.

NOTES

• Kit contains the appropriate core & coil with color coded leads, a properly rated capacitor and ignitor (if required) and all other components required for ballast replacement

GENERAL CHARACTERISTICS

Lamp Type Bulb Ballast Type Туре Dimming Type Starting Method Lamp Wiring Line Voltage Regulation (+/-) Ambient Temperature (MIN) Ambient Temperature (MAX) Ballast Factor Circuit Type Insulation Class Enclosure Type Capacitance Capacitor Temperature Rating Distance to Lamp (MAX)

HID -Magnetic Metal Halide Core and Coil Replacement kit N/A Pulse start Series 10.0 % -30.0 °C 105.0 °C 1 HX-HPF UL Class H 180 Core and Coil 12.0 µF 100.0 °C 5.0 ft

ELECTRICAL CHARACTERISTICS

Lamp Operating Frequency Supply Current Frequency Voltage (MIN)

DIMENSIONS

Weight Exit Type Diameter Nominal Length Frame size (H x L)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 86675 GEM100MLTLA3D-5 Master

1.600 in(40.6 mm)

2.700 in(68.6 mm)

NaN in(NaN mm)

6 Distributor Kit 1 6

60.0 Hz

60.0 Hz

280.0

4.8 lb

043168866750