



GE
Lighting

43130 - Integrated U6 LED Plastic Tubes

LED13ET8/U6/850

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ LED tubes are ideal for those seeking high energy savings with minimal installation time.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ GE integrated LED tubes run on electronic T8 instant-start or programmed start ballasts.
- ☞ Shatter resistant
- ☞ No UV
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed

Product Photo



CAUTIONS & WARNINGS

Caution

Risk of Electric Shock

Suitable for damp locations

Not intended for use with emergency exit fixtures or emergency exit lights

GENERAL CHARACTERISTICS

Dimmable	Yes
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	Yes
LED Tube Type	Plastic
Environmental Rating	LED_Tube_Plastic
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.57
Bulb Shape	T8-U6

PHOTOMETRIC CHARACTERISTICS

Rated Beam Spread	13 W
Initial Lumens-nominal	1800 lm
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	43130
Description	LED13ET8/U6/850
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	
Standard Package GTIN	10043168431306
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	22.5 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Drive Current	45.7
Energy Efficiency Class	yr
Voltage <Nom>	120 V
Rated power (Watts)	13 W