

170-03136



**Article Number:** 170-03136

**Split Wrap Braided Sleeveing, 1.0" ID, PET, Black, 400.0 ft/Large Bulk Reel**



## Base Data

**Local Order Number** 170-03136

**Type** BSPSW100LB

**Color** Black (BK)

**Features and Benefits**

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

**Product Description** A lateral split, semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

**Open Post Termination** No

**Short Description** Split Wrap Braided Sleeveing, 1.0" ID, PET, Black, 400.0 ft/Large Bulk Reel

## Product Dimensions

**Length L (imperial)** 400.0 ft

**Length L (metric)** 121.9 m

**Bundle Diameter max (imperial)** 1.0 "

**Bundle Diameter max (metric)** 25.4 mm

**Nominal Diameter (imperial)** 1.0 "

**Nominal Diameter (metric)** 25.4 mm

## Logistics and Packaging

**Quantity per** reel

**Package Quantity (imperial)** 400 ft

**Package Quantity** 400.0 ft

**Reel Length (metric)** 121.9 m

**Reel Length (imperial)** 400.0 ft

**Weight (imperial)** 8.0 lbs

**Weight (Metric)** 3.6 kg

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL94 V0

**Melting Point** +250 °C

**Operating Temperature** -94 °F to +257 °F (-70 °C to +125 °C)

**ROHS Conformity** Yes

**UL Recognized (US and Canada)** Yes