

## T50MR9C2



**Article Number:** 113-05004

**Screw Mount Tie, 50 lb 8.5" Max Bundle Diameter 1.8", #10 Screw, PA66, Natural, 100/pkg**



### Base Data

<b>Local Order Number</b>	T50MR9C2
<b>Type</b>	T50MR
<b>Color</b>	Natural (NA)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Mount design secures firmly with any #10 Screw.</li> <li>• Screw mount style creates low insertion and high extraction force.</li> </ul>
<b>Product Description</b>	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
<b>Fixation Method (FF)</b>	fixing hole
<b>Identification Plate Position</b>	none
<b>Releasable Closure (Yes/No)</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Short Description</b>	Screw Mount Tie, 50 lb 8.5" Max Bundle Diameter 1.8", #10 Screw, PA66, Natural, 100/pkg

### Product Dimensions

<b>Minimum Tensile Strength (imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (N)</b>	225 N
<b>Length L (imperial)</b>	8.5 "
<b>Length L (metric)</b>	215.0 mm
<b>Width W (imperial)</b>	0.18 "
<b>Width W (metric)</b>	4.7 mm
<b>Height H (imperial)</b>	0.22 "
<b>Height H (metric)</b>	5.7 mm
<b>Bundle Diameter min (imperial)</b>	0.06 "
<b>Bundle Diameter min (metric)</b>	1.5 mm
<b>Bundle Diameter max (imperial)</b>	1.8 "
<b>Bundle Diameter max (metric)</b>	45.0 mm
<b>Mounting Hole Diameter D (imperial)</b>	0.21 "
<b>Mounting Hole Diameter D (metric)</b>	5.4 mm
<b>Thickness T (imperial)</b>	0.05 "
<b>Thickness T (Metric)</b>	1.2 mm

### Logistics and Packaging

<b>Quantity per</b>	bag
<b>Package Quantity</b>	100

Carton Quantity 5000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes