



Sensors: Motion & Presence Detectors

IOS-CMP-DT-LV | Low-Voltage Ceiling Mount Dual Tech Sensor

IOS-CMP-DT-LV

LOW-VOLTAGE CEILING MOUNT DUAL TECH SENSOR

This ceiling mount sensor detects presence using a combination of Passive Infrared (PIR) and ultrasonic technologies, and in conjunction with a remote power pack unit, turns the load ON and OFF when presence is detected.



Features & Applications

Features

- Ultrasonic and PIR sensing for presence detection, even in areas with partitions and/or with small movements
- Low-voltage, ceiling mounted sensor
- Coverage: 360°, 1600 ft² PIR, 1000 ft² Ultrasonic mounted on 8 to 11 ft ceiling
- Adjustable time delay
- Adjustable ambient light sensor override
- Powered by IOS-PP24 power pack, sold separately


Applications

- Partitioned Restroom
- Storage Rooms
- Waiting Rooms

Specifications

Occupancy Sensor Power Type	Maximum Current Consumption (mA)	Operating Temperature Min (F)
Low Voltage	20	32
Sensor Technology	PIR Coverage Pattern (degrees)	Product Height (in)
Dual Technology (PIR/Ultrasonic)	360	1 3/8
Mount Type	Adjustable Light Level Max	Product Height (mm)
Ceiling	Daylight	35
Neutral Connection Required	Adjustable Light Level Min	Product Diameter (in)
No	10 fc	4 9/16
Sensor Switch Type	Operating Temperature Max (°C)	Product Diameter (mm)
Occupancy	50	116
Color	Operating Temperature Max (F)	Warranty
White	122	2-year limited
Number of Circuits	Operating Temperature Min (°C)	
0	0	

Related Accessories and Parts (1)



IOS-PP24

LOW-VOLTAGE POWER PACK

Copyright © 2017 Intermatic Incorporated. All rights reserved.