





UPC Code: 07847796957

Country Of Origin: United States

NEMA: L6-15R



# 25W49

#### **Brand Features**

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

#### **Item Description**

15 Amp, 250 Volt, NEMA L6-15R, 2P, 3W, Locking Connector, Industrial Grade, Grounding, Wetguard - YELLOW

#### **Technical Information**

Electrical Specifications
Grounding: Grounding
Amperage: 15 A
Voltage: 250 VAC

Pole: 2 Wire: 3

Dielectric Voltage: Withstands 2000V

per UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 60°C

Environment: Wet

Material Specifications

Body Material: EPTR Rubber

Body Interior: Nylon

Compression Nut, Strain Relief: Nylon

Wire Module: Nylon
Bushing: Santoprene TPV

Blades/Contacts: Nickel-Plated Brass Terminal Screws: Electroless Nickel-

coated Brass

Assembly Screws: Stainless Steel 300

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: 18-10 AWG
Product ID: Ratings and NEMA I.D.
permanently marked on device
Cord Grip Range (in): .234-.687

Product Features
NEMA: L6-15R

Blades/Contacts: Nickel-Plated Brass

Body Material: EPTR Rubber

Assembly Screws: Stainless Steel 300 Standards and Certifications: UL/CSA

Color: Yellow Brand: Wetguard

**Device Type:** Locking Connector

Standards and Certifications


**NEMA:** WD-6 **ANSI:** C-73

CSA C22.2 No. 42: File LR-406


**NOM:** 057

Warranty: Lifetime Warranty

## **Dimensional Diagram**



## Wiring Diagram



# L6-15R

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

