

80054

## Lampholders



[Additional Views](#)

UPC Code: 07847783352

Country of Origin: Please Contact Customer Service

### Product Lists

[Add to Product List](#)

[View Product List](#)

Quantity:



### Item Description

Miniature Bi-Pin Base, G4, G6.35, GY6.35, GX5.3 MR16, GZ4 MR11, Halogen, Incandescent, Ceramic Body Lampholder, Mounting Holes, , Side Wired, - White

### Where To Buy

Find a Store

Market Channel

[Technical Information](#) | [Features and Benefits](#) | [Support](#) | [Discussions](#)

### Technical Information

[TOP](#)

#### Electrical Specifications

Max. Wattage Rating: 750W  
 Max. Voltage: 250 Volt  
 Max. Amperage: 12 Amp

#### Material Specifications

Body Material: Ceramic Body  
 Cover Material: Mica  
 Contact Material: Nickel-Plated Copper-Alloy  
 Color: White  
 Availability: OEM Only

#### Mechanical Specifications

ANSI Lamp Type: G4, G6.35, GY6.35, GX5.3 MR16, GZ4 MR11  
 Lamp Socket Base: Miniature Bi-Pin  
 Access: Side Wired  
 Termination: 12-Inch 18GA SEW-1 200C Wire Leads  
 Wire Strip Length: 1/2 Inch

#### Product Features

Lamp Socket Base: Miniature Bi-Pin  
 ANSI Lamp Type: G4, G6.35, GY6.35, GX5.3 MR16, GZ4 MR11  
 Mounting Type: Mounting Holes  
 Access: Side Wired  
 Termination: 12-Inch 18GA SEW-1 200C Wire Leads  
 Standards and Certifications: UL/CSA  
 Warranty: 1 Year Limited  
 Availability: OEM Only

#### Standards and Certifications

UL Recognized: Component E13405  
 CSA Certified: File LR-1863

### Features and Benefits

[TOP](#)

- **WARNING:** Miniature Quartz Halogen Lamps operate under pressure and high temperatures. To prevent socket damage, the design of the fixture and its application must be carefully considered. For Leviton warranties to apply to this product, lamp wattage, current and beam spread must be controlled to insure that the following temperature limits are never exceeded.
- At contacts within socket - 225C
- Socket lead wires - 200C
- **NOTE:** Maximum rating of 250C available when appropriately rated leads are used.

### Support

[TOP](#)