

CS6364C



Color: Black-White

UPC Code: 07847732621

Country Of Origin: Mexico

NEMA:
Non-NEMA



Brand Features

Leviton's Black &White 50 Amp, Non-NEMA line of industrial grade locking blade devices feature rugged construction that resists impact, sunlight, chemicals and rough use. All contacts and blades are solid one-piece construction for superior conductivity. Corrosion resistant versions feature nickel plated contacts and blades, plus stainless steel shrouds and screws. The ergonomic, fluted-body design with radial gripping edge is ideal for gripping and pulling. The unique cord clamp accepts a wide range of cord sizes, providing a secure grip without damaging the cord. And, they are backed by a limited lifetime warranty.

Item Description

50Amp, 125/250V AC, Non-NEMA, 3P, 4W, Black &White Locking Connector, Industrial Grade, Grounding, California-Style(CS) – BLACK-WHITE

Technical Information

Electrical Specifications

Grounding: Grounding

Amperage: 50 A

Voltage: 125/250 VAC

Pole: 3

Wire: 4

Dielectric Voltage Withstand: 2000V minimum per UL 498

Maximum Working Voltage: 125/250V as rated

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rise: Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

Environmental Specifications

Flammability: Rated HB or better UL94

Operating Temperature: -40°C to 75°C

Environment: Dry

Material Specifications

Face Module: Nylon

Wiring Chamber: Nylon

Assembly Screws: Brass

Housing Material: Nylon

Dust Shield: Santoprene TPE

Terminal Block: 0.062inch thick Copper

Terminal Set Screw: SS 302/304

Ground Shunt: Bronze

Ground Post: Brass

Contact - Spring Value: 0.041inch thick Brass

Contact - Binding Plate: 0.100inch thick Brass

Contact Rivet: Brass

Center Pin: SS 302/304

Standard Cable Clamp: Nylon

Cable Clamp Screw: Philips Head, SS 304

Color: Black-White

Mechanical Specifications

Terminal ID: X, W, Y, Z and Green for ground

Terminal Accom.: #10 min to #4max AWG Solid or Stranded Wire

Product ID: Ratings and Catalogue No. molded into face and stamped into shroud

Cord Range: .680 - 1.125

Product Features

NEMA: Non-NEMA

Color: Black-White

Device Type: Locking Connector

Brand: Black and White

Standards and Certifications


UL 498: File E13399

CSA C22.2 No. 42: File 152105

NOM: 057

RoHS: Compliant

Warranty: Lifetime Limited



SPECIFICATION SUBMITTAL

JOB NAME:		CATALOG NUMBERS:	
<input type="text"/>		<input type="text"/>	<input type="text"/>
JOB NUMBER:		<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

