



Warm Whispering Caramel

Wheat

White on White

RUAA1-CA

Renu 3.6A USB Type-A/Type-A Wall Outlet Charger with 15A Tamper-Resistant Receptacle

Combination Duplex Receptacle/Outlet and USB Charger. 15 Amp, 125 Volt, Renu Tamper-Resistant Receptacle/Outlet, NEMA 5-15R. 3.6 Amps, 5VDC, 2.0 Type A USB Chargers. Grounding, Side Wired & Back Wired – Café Latte

- SMART - Built-in smart chip recognizes the individual device's charging

requirement to optimize the charge

- POWERFUL Two high-powered charging ports with 3.6A of charging power
- CONVENIENT No more searching for charging adapters! Upgrade your existing outlets so you can charge up to two USB powered electronics at once, leaving the outlets free for additional power needs
- EASY Matte finish available in 20 popular colors that works with Leviton Renu wallplate REWP1/REWP2/REWP3/REWP4

Technical Information

Product Features Amperage: 15 A Brand : Renu Color : Cafe Latte Color Change Kit : RKAA1 **Device Type : USB Duplex Outlet** Grade : Residential Grounding : Self-Grounding Clip and Green Ground Screw Horsepower Rating: 15A-1/2 HP **NEMA : 5-15R** Ratings: 15A-125V Type : Type A/A Duplex Receptacle Voltage: 125 VAC Wallplate : Not Included

Electrical Specifications Amperage: 15 A Flammability : Rated V-0 per UL 94 Grounding : Self-Grounding Clip and Green Ground Screw Horsepower Rating: 15A-1/2 HP Operating Temperature : -10°C to 40°C Ratings: 15A-125V **Environmental Specifications**

Body Material : Thermoplastic **Cover Material : Thermoplastic** Flammability : Rated V-0 per UL 94 Operating Temperature : -10°C to 40°C

Features and Benefits

Strap Material : Steel Material Specifications Body Material : Thermoplastic **Cover Material :** Thermoplastic Product ID : Stamped on Strap Strap Material : Steel Terminal Accom.: 14-12 AWG Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd Termination : Back & Side Torque Range: 14 - 18 in.-lbs

Mechanical Specifications Color : Cafe Latte Color Change Kit : RKAA1 Device Type : USB Duplex Outlet Grade : Residential **NEMA : 5-15R** Product Family : Renu Product ID : Stamped on Strap Terminal Accom. : 14-12 AWG Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd Termination : Back & Side Torque Range: 14 - 18 in.-lbs

Standards and Certifications FCC Part 15 : Class B Listed : cCSAus NOM: 057 Warranty: 5-Year Limited



- Smart chip recognizes and optimizes the charging requirements of individual

devices

- 3.6A charging capacity
- Two high-powered charging ports
- Two 15A or 20A Tamper-Resistant receptacles for improved safety
- USB ports are positioned vertically providing more space for maneuvering and reducing stress on USB cables
- Compatible with USB 2.0 devices
- Fits in a standard wallbox
- Back and side wired for easy installation
- Can replace existing outlets Can be multi-ganged with Renu devices
- Available in 20 popular colors to match any décor
- Once installed, face easily snaps OFF and ON. Change color by ordering the
- RKAA1 or RKAA2 color change kit
- Uses only Renu Wallplates (sold separately)

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

