

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings L3 and L3R.

CONSTRUCTION

White aluminum one piece reflector with narrow integral flange.

White eyelid faceplate.

INSTALLATION

Socket to trim interface.

Retaining clips pull and snap onto top of reflector to hold trim inside housing.

LISTINGS

UL Listed to US and Canadian safety standards.

Damp location listed.

Patent on clip. Patent No. (US) 5707143, (Canada) 2193902.

WARRANTY

1-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Actual performance may differ as a result of end-user environment and application.

Note: Specifications subject to change without notice.


Catalog Number
Notes
Type

4" Finishing Trim

3W1

WALLWASH

Narrow Flange




Specifications

Height: 3 (7.6)

Lamp opening: 1-1/2 (3.8)

Diameter: 4-7/8 (12.4)



All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 3W1

3W1	
Series	Finish
3W1	(blank) White

Housing Compatibility: Housing and trim ordered separately.

Application	Source	Maximum wattage	Housing
IC	Incandescent	35 PAR20	L3, L3R
		50 R20	

