

EASY-WRAP™

# High Voltage, Glass Cloth & Rubber Mastic Tape

EWHR, EWGC, EWMT SERIES



## HIGH VOLTAGE RUBBER TAPE - 69 KV WITH WHITE LINER

- Self bonding, highly conformable 30 mil EPR rubber with liner.
- Use as primary electrical insulation for applications through 69 KV.
- Flame Retardant, IEEE Standard 17-1974 ANSI.

### TEMPERATURE RATING:

Rated for 90 °C (194 °F) continuous operating temperature. Intermittent to 130 °C (266 °F). Will not crack at -40 °C (-40 °F).

CAT. NO.	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
<b>EWHR 307530-L</b>	30	0.750	0.030	1
<b>EWHR 3010030-L</b>	30	1.000	0.030	1
<b>EWHR 3015030-L</b>	30	1.500	0.030	1
<b>EWHR 3020030-L</b>	30	2.000	0.030	1

## GLASS CLOTH RUBBER ADHESIVE

- Provides heat stabilized insulation for applications where resistance to high temperature and high mechanical strength are required, such as motor leads, hot spots, switches and controls.

### TEMPERATURE RATING:

Insulation Class: 130 °C (266 °F).  
Dielectric strength: 3,300 Volts.  
MIL-I-15126F (type GFT).



CAT. NO.	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
<b>EWGC75066</b>	66	0.500	0.007	1
<b>EWGC77566</b>	66	0.750	0.007	1

## LINED RUBBER MASTIC TAPE

- A self-fusing conformable electrical insulating and sealing tape.
- EPR rubber with a strong stable mastic adhesive for busbar and splice connections.

### TEMPERATURE RATING:

130 °C (266 °F).



CAT. NO.	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
<b>EWMT 1252524</b>	2	2.500	0.125	1

WIRE MANAGEMENT