

WIRE MANAGEMENT

Thin-Wall Tubing

Easy-Splice™

TWHS Series



SPECIFICATIONS

- UL Recognize.
- Temperature Rating: 125 °C. 600V Max.
- Black, White and colored thin-wall tubing meet MIL-DTL-23053/5, Class 1.
- Clear meets MIL-DTL-23053/5, Class 2 and is not flame retardant.

FEATURES

- Flexible flame-retardant, thin wall, general purpose heat-shrinkable polyolefin tubing has a 2:1 shrink ratio.
- Used for electrical insulation, wire harness bundling, wire jacket marking and color coding, it also splices and makes functional terminations.
- Standard packaging is either 6" lengths in blister boxes, or in economical 25' spools.

CAT. NO.	EXPANDED I.D.	RECOVERED I.D.	NOMIINAL RECOVERED WALL THICKNESS	LENGTH (IN./FT.)	STD. PKG. QTY.
TWHS-046-6	0.046	0.230	0.016	6"	15
TWHS-046-48	0.046	0.230	0.016	48"	1
TWHS-063-6	0.063	0.031	0.017	6"	15
TWHS-063-48	0.063	0.031	0.017	48"	1
TWHS-063-25B	0.063	0.031	0.017	25' Spool	1
TWHS-093-6	0.093	0.046	0.020	6"	15
TWHS-093-48	0.093	0.046	0.020	48"	1
TWHS-093-25B	0.093	0.046	0.020	25' Spool	1
TWHS-125-6	0.125	0.062	0.020	6"	15
TWHS-125-48	0.125	0.062	0.020	48"	1
TWHS-125-25B	0.125	0.062	0.020	25' Spool	1
TWHS-187-6	0.187	0.093	0.020	6"	12
TWHS-187-48	0.187	0.093	0.020	48"	1
TWHS-187-25B	0.187	0.093	0.020	25' Spool	1
TWHS-187	0.187	0.093	0.020	1,000' Spool	1
TWHS-250-6	0.250	0.125	0.025	6"	10
TWHS-250-48	0.250	0.125	0.025	48"	1
TWHS-250-25B	0.250	0.125	0.025	25' Spool	1
TWHS-250	0.250	0.125	0.025	500' Spool	1