



METAL CLAD (MC) CONNECTORS SADDLE-TYPE

Features:

- Zinc Die Cast
- Combo Head Set-Screw
- With Insulated Throat
- Suitable for Dry Location Only

Note:

- Insulated color may vary



Cat. No.	Description	Trade Size	Std. Pkg.	Master Ctn.
OF6231	AC & MC Interlocking Steel 0.450 to 0.590 Dia.	1/2"	100	500
	AC & MC Interlocking AL 0.440 to 0.600 Dia.			
	Round Corrugated AL, MC 0.574 to 12/4			
	Square Corrugated AL, MC 0.527, 0.254, 12/3			
OF6232	AL FMC, 3/8" Steel and RW FMC, 3/8" Steel	3/4"	50	250
	Interlocking Steel 0.661 to 0.711 Dia.			
	Interlocking AL 0.775 to 0.825 Dia.			
	AC, AL, & Steel 0.650 to 0.810 Dia. & Flex, 1/2" Steel			

METAL CLAD (MC) & AC (BX) CONNECTORS SET-SCREW TYPE

Features:

- Zinc Die Cast
- For Steel Only



Cat. No.	Description	Trade Size	Std. Pkg.	Master Ctn.
OF653	AC, Steel, 14/2 AWG and MC 0.500 to 0.550 dia.	1/2"	100	500

METAL CLAD (MC) & AC (BX) CONNECTORS

Features:

- Zinc Die Cast
- For Steel and Aluminum



Cat. No.	Description	Trade Size	Std. Pkg.	Master Ctn.
OF6620	AC (BX) 14/2 to 10/2, MC 14/2 to 10/3	1/2"	100	500

METAL CLAD (MC) CONNECTORS CLAMP TYPE

Features:

- Zinc Die Cast
- With Insulated Throat
- Suitable for dry location only

Note:

- Insulated color may vary



Cat. No.	Description	Trade Size	Std. Pkg.	Master Ctn.
MC-CL-100		1"	10	100
MC-CL-125		1-1/4"	25	100
MC-CL-150		1-1/2"	10	100
MC-CL-200		2"	10	100
MC-CL-250		2-1/2"	-	10
MC-CL-300		3"	-	5
MC-CL-350		3-1/2"	-	5

COMBINATION AC (BX) & NON-METALLIC(NM) CONNECTORS

Features:

- Zinc Die Cast



Cat. No.	Description	Trade Size	Std. Pkg.	Master Ctn.
OF623	14/2 AC(BX), 14/2 NM, 0.340 to 0.380 dia cord 14/3 & 14/3 SJO, 16/2 SO	1/2"	25	250