

# EAST HAVEN

Wall mount • Wet location listed



## Specifications:

### Description:

Medium LED Wall lantern with contemporary styling and clear seeded glass. 120V AC replaceable LED module, 623 lumens, 3000K color temperature and 90+ CRI.

### Construction:

- Antique Bronze (-20) (powdercoat)
- Aluminum construction Clear Seeded glass LED Module is replaceable (part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Title 24 compliant
- Back plate covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- Six inches of wire supplied

### Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

## P6078-2030K9

### Images:



### Dimensions:

Width: 7-1/2"  
 Height: 9-3/4"  
 Depth: 9-1/8"  
 H/CTR: 4-3/4"

### Catalog number:

Base	Finish	Color Temp	CRI
P6078	20 - Antique Bronze	30K - 3000K	9 - 90 CRI

## P6078-2030K9

### Dimming Notes:

---

P6078 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

#### Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.