



Indoor fixtures for use below 25'. 16" units for 250w Metal Halide. 22" units for 400w Metal Halide. Die cast aluminum housing, wiring box and semi specular anodized aluminum refractor. Ballast and lamp supplied.

Color: White

Weight: 19.5 lbs

Project:	Type:
Prepared By:	Date:

Lamp Info		Ballast Info	
Type	ED28	Type	CWA-HPF QT
Watts	250W	120V	1.4/2.5A
Shape/Size	N/A	208V	.8/1.5A
Base	N/A	240V	.7/1.3A
ANSI	N/A	277V	.6/1.1A
Hours	15,000	Input Watts	278W
Lamp Lumens	23,800		
Efficacy	85.6 lm/W		

Technical Specifications

Compliance

UL Listed:

UL Listed for 65° C (149° F) ambient temperature. Damp locations.

Construction

Housing:

Heavy die-cast aluminum housing with powder coat finish

Junction Box:

Heavy duty stamped steel junction box

Plate:

Die-cast plate tapped 3/4" NPS accepts 3/4" pipe or 715NEW die cast hook

Reflector:

Reflector with five distribution patterns for precise control

Electrical

Socket:

Mogul base open rated socket

Ballast:

Quad Tap. All fixtures are wired for 277V at the factory.

Wiring Compartment:

Removable steel wiring compartment door for quick and easy mounting

Start Up Time:

3 - 5 minutes

Restrike Time:

10 - 20 minutes

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code [More info](#).

Optical

Patterns:

Field adjustable light distribution patterns

Lamp:

Mogul Base, ED18

Technical Specifications (continued)

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- CSA Certified for Indoor Locations
- Supplied with safety hook and 3 foot cord
- Use indoors below 25'
- Ballast and lamp included