BLH400P22DLPSQ





Indoor fixtures for use below 25'. 16" units for 250w Metal Halide. 22" units for 400w Metal Halide. Die cast aluminum housing and wiring box. Clear acrylic Lexalite Reflexor prismatic refractor. Ballast and lamp supplied.

Color: Prismatic Weight: 35.8 lbs

Project:	Туре:
Prepared By:	Date:

Lamp Info		Ballast	Ballast Info	
Туре	ED37	Type	CWA-HPF QT	
Watts	400W	120V	3.5/4.0A	
Shape/Size	N/A	208V	2.0/2.3A	
Base	N/A	240V	1.8/2.0A	
ANSI	N/A	277V	1.5/1.8A	
Hours	20,000	Input Watts 449W		
Lamp Lumen:	s 41,000			
Efficacy	91.3 lm/W			

Technical Specifications

Compliance

UL Listed:

UL Listed for 65° C (149° F) ambient temperature. Damp locations.

Construction

Housing:

Heavy die-cast aluminum housing with powder coat finish

Junction Box:

Heavy duty stamped steel junction box

Plate:

Die-cast plate tapped 3/4" NPS accepts 3/4" pipe or 715NEW die cast hook

Reflector:

Reflector with five distribution patterns for precise control

Bracket:

Multi-position adjustable reflector bracket

Electrical

Socket:

Mogul base open rated socket

Ballast:

Quad Tap. All fixtures are wired for 277V at the factory.

Wiring Compartment:

Removable steel wiring compartment door for quick and easy mounting

Start Up Time:

3 - 5 minutes

Restrike Time:

10 - 20 minutes

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code <u>More info</u>.

Optical

Patterns:

Field adjustable light distribution patterns



Technical Specifications (continued)

Optical

Lamp:

Mogul Base, ED18

Refractor:

Seven distribution patterns for precise control with seven position adjustable bracket. Clear acrylic Lexalite Reflexor_ prismatic refractor for long-term resistance to yellowing.

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.



Features

CSA Certified for Indoor Locations
Supplied with safety hook and 3 foot cord
Use indoors below 25'
Ballast and lamp included