PS4-11-25D2

RAB



Technical Specifications

Compliance	Color:	Shaft Size:
CSA Listed:	Bronze powder coating	4"
Suitable for wet locations	Height:	Hand Hole Dimensions:
Construction	25 FT	3" x 5"
Shaft:	Weight:	Bolt Circle:
46,000 p.s.i. minimum yield.	168 lbs	8 1/2"
Hand Holes:	Gauge:	Base Dimension:
Reinforced with grounding lug and removable	11	8"
cover	Wall Thickness:	
Base Plates:	1/8"	
36,000 p.s.i. minimum yield.		
Shipping Protection:		
All poles are shipped in individual corrugated cartons to prevent finish damage		

Technical Specifications (continued)

Construction


Anchor Bolt:

Galvanized anchor bolts and galvanized hardware and anchor bolt template. All bolts have a 3" hook.

Anchor Bolt Templates:

WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available <u>online</u>.

Dimensions



Pre-Shipped Anchor Bolts:

Bolts can be pre-shipped upon request for additional freight charge

Max EPA's/Max Weights:

70MPH 4.3 ft./275 lb. 80MPH 1.7 ft./270 lb

Other

Terms of Sale:

Pole Terms of Sale is available online.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Features

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Pole caps, base covers & bolts are sold separately

Custom manufactured for each application