

# Product data sheet

## Characteristics

# 10285

## Multi 9 - comb busbar - 1P - type 1L - 18 mm pitch - 12 modules - 100A

Product availability : Stock - Normally stocked in distribution facility



### Main

Range	Multi 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	1P
Number of ways	12 ways, type : 1 L (tooth) with 18 mm pitch
Distance between way	0.71 in (18 mm)
Marking	L
Total number of 18 mm modules	12

### Complementary

Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	100 A ( 40 °C )
System Voltage	277 V AC Ph/N 480 V AC Ph/Ph
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Width	8.5 in (216 mm)
Colour	Light grey ( RAL 7035 )
Range compatibility	Multi 9 / Multi 9 C60 / C60SP

### Environment

Standards	UL 1077 IEC 60947-2
-----------	------------------------

GB 14048.2

Fire resistance	1760 °F (960 °C) ( 30 s )
-----------------	---------------------------

### Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901842378
Nbr. of units in pkg.	1
Package weight(Lbs)	0.17000000000000001
Returnability	Y
Country of origin	DE

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0726 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------