

# Product data sheet

## Characteristics

# 10S1F

## TRANSFORMER DRY 10KVA

### 240X480V-120/240V

Product availability : Stock - Normally stocked in distribution facility



Price\* : 2712.00 USD



### Main

|                           |                        |
|---------------------------|------------------------|
| Product or component type | Dry Sealed Transformer |
| Primary voltage           | 240 x 480 V            |
| Secondary voltage         | 120/240 V              |
| Number of tap-offs        | 0                      |

### Complementary

|                    |                         |
|--------------------|-------------------------|
| Box number         | 13B                     |
| Phase              | 1 phase                 |
| Primary voltage    | 240 x 480 V : 120/240 V |
| Rated power in VA  | 10 kVA                  |
| Temperature rise   | 115 °C                  |
| Height             | 14.75 in                |
| Width              | 9.75 in                 |
| Depth              | 11.75 in                |
| Enclosure mounting | Wall mounted            |
| Enclosure material | Painted sheet steel     |

### Environment

|                           |                           |
|---------------------------|---------------------------|
| NEMA degree of protection | NEMA 3R                   |
| Insulation temperature    | 356 °F (180 °C)           |
| Product certifications    | UL listed<br>cULus<br>CSA |

### Ordering and shipping details

|          |                         |
|----------|-------------------------|
| Category | 16277 - RESIN LVGP XFMR |
|----------|-------------------------|

|                       |                |
|-----------------------|----------------|
| Discount Schedule     | PE2            |
| GTIN                  | 00785901359562 |
| Nbr. of units in pkg. | 1              |
| Package weight(Lbs)   | 165            |
| Returnability         | Y              |
| Country of origin     | MX             |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1430 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|