

Product availability : Stock - Normally stocked in distribution facility



Price* : 1190.00 USD



Main

Range of product	Modicon Quantum automation platform
Product or component type	Fibre converter
Optic fiber type	Multi mode

Complementary

Bus current requirement	1000 mA
Power dissipation in W	5 W
Inrush current	1 Aat 5 V DC
Number of port	2 fiber optic, connector type: LC 2 Ethernet, connector type: RJ45
Local signalling	1 LED green module status with RDY marking 1 LED red internal fault, module failure with ERR marking 1 LED green channel 1 link status with STS1 marking 1 LED green channel 1 communication status with FX1 ACT marking 1 LED green channel 2 link status with STS2 marking 1 LED green channel 2 communication status with FX2 ACT marking
Wavelength	5.1575E-05 in (1310 nm)
Optic distance between 2 transceivers	6561.68 ft (2000 m) (50/125 µm), optical power : -23.5...-14 dBm 9842.52 ft (3000 m) (62.5/125 µm), optical power : -20...-14 dBm
Attenuation	-23.5...-14 dB (50/125 µm) -20...-14 dB (62.5/125 µm)
Rise/Fall time	3 ns
Receiver sensitivity	- 30 dBm
Detected silence	-45 dBm
Marking	CE
Material	PC (polycarbonate)
Width	1.59 in (40.34 mm)
Height	9.84 in (250 mm)
Depth	4.09 in (103.85 mm)

Product weight	1.22 lb(US) (0.554 kg)
----------------	------------------------

Environment

Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	<= 95 %
Operating altitude	0...6561.68 ft (0...2000 m)
Standards	CSA C22.2 No 142 FM Class 1 Division 2 UL 508
Product certifications	Merchant Navy C-Tick TÜV

Ordering and shipping details


Category	18155 - QUANTUM I/O & POWER SUPPLIES
Discount Schedule	PC21
GTIN	00785901762416
Nbr. of units in pkg.	1
Package weight(Lbs)	1.3100000000000001
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1623 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots