

Product data sheet

Characteristics

3S1F

TRANSFORMER DRY 3KVA

240X480V-120/240V

Product availability : Stock - Normally stocked in distribution facility



Price* : 1144.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary voltage	240 x 480 V
Secondary voltage	120/240 V
Number of tap-offs	0

Complementary

Box number	10A
Phase	1 phase
Primary voltage	240 x 480 V : 120/240 V
Rated power in VA	3 kVA
Temperature rise	115 °C
Height	10.5 in
Width	8.62 in
Depth	6.5 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CSA UL listed cULus

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
----------	-------------------------

Discount Schedule	PE2
GTIN	00785901359418
Nbr. of units in pkg.	1
Package weight(Lbs)	59.78000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------