

# Product data sheet

## Characteristics

# 60955

ground fault protector GFP - 2 poles - 63A -  
120..240V - 30mA SIE

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1001.00 USD



### Main

Range	Multi 9
Product name	Multi 9 GFP
Product or component type	Residual current circuit breaker (RCCB)
Device short name	GFP
Poles description	2P
Neutral position	Left
[In] rated current	63 A 104 °F (40 °C)
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC-SIE
Rated conditional short-circuit current	10 kA
Utilisation category	AC-23A

### Complementary

Network frequency	50/60 Hz
System Voltage	230/240 V AC 50 Hz 120/240 V AC 60 Hz
[Uimp] rated impulse withstand voltage	6 kV
Control type	Toggle
Local signalling	Fault indication
Connection pitch	0.71 in (18 mm) : Between phases
9 mm pitches	4
Colour	Grey
Mechanical durability	20000 cycles
Provision for padlocking	Padlockable

Locking options description	Padlocking in OFF position
Connections - terminals	Tunnel type terminals 0...0.05 in <sup>2</sup> (2.5...35 mm <sup>2</sup> ) flexible Tunnel type terminals 0...0.05 in <sup>2</sup> (2.5...35 mm <sup>2</sup> ) rigid
Wire stripping length	0.14 in (3.5 mm)

## Environment

Standards	IEC 61008 UL 1053
IP degree of protection	IPxx B conforming to IEC 60529 IP20 conforming to IEC 60529 IP40 conforming to IEC 60529
Tropicalisation	2
Relative humidity	95 % ( 131 °F (55 °C) )
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)

## Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901618775
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5
Returnability	N
Country of origin	ES

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0830 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------