Product data sheet Characteristics

8501CDO16V53 **RELAY 600VAC 5AMP TYPE C +OPTIONS**

Product availability: Stock - Normally stocked in distribution facility



Price*: 70.00 USD



Main

Main		
Range of product	Power Relay 8501C	
Product or component type	Power relay	
Device short name	Type C	
Line Rated Current	30 A	
Device application	Suited for controlling small single phase motors and other light loads	
Rated power in hp	1.5 hp	
Maximum switching voltage	600 V AC	
Complementary		
Catalog class	8501	
Switch function	DPDT	
Contacts type and composition	2 NO/2 NC	
Mounting support	Panel mounting	
Phase	1 phase	
Connections - terminals	Screw clamp terminal	
Environment		
Environment Product certifications	CE	
Froduct certifications	CSA	
	UL listed	
Ambient air temperature for operation	-22140 °F	
Ordering and shipping details		
Category	21131 - 8501 C	
Discount Schedule	CP2	
GTIN	00785901052197	
Nbr. of units in pkg.	1	
Con 00, 2047		

Complementary

Catalog class	8501
Switch function	DPDT
Contacts type and composition	2 NO/2 NC
Mounting support	Panel mounting
Phase	1 phase
Connections - terminals	Screw clamp terminal

Environment

Product certifications	CE CSA UL listed
Ambient air temperature for operation	-22140 °F

Ordering and shipping details

Category	21131 - 8501 C
Discount Schedule	CP2
GTIN	00785901052197
Nbr. of units in pkg.	1

Package weight(Lbs)	0.60999999999999	
Returnability	Υ	
Country of origin	CN	
Offer Sustainability		
Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	

Contractual warranty

Contractadi Warranty		
Warranty period	18 months	