

Product availability : Stock - Normally stocked in distribution facility



Price\* : 408.00 USD



### Main

Range of product	8501X
Relay type	Latching
Product or component type	Relay
[In] rated current	10 A AC 5 A DC
Contacts type and composition	6 NO 6 standard contact cartridges
Poles description	6P
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Maximum switching voltage	600 V AC
Mounting support	Panel
Ambient air temperature for operation	-40...160 °F
Electrical connection	Screw clamp terminals
Product certifications	CE CSA UL listed
Operating time	15 ms pick-up 13 ms drop-out

### Ordering and shipping details

Category	21158 - 8501 XO (AC)
Discount Schedule	CP2
GTIN	00785901028512
Nbr. of units in pkg.	1
Package weight(Lbs)	3.3000000000000003
Returnability	N
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1332 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------