

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1367.00 USD



### Main

Product or component type	Combination Starter
Range of product	S
Control circuit	Separate control circuit
Control type	No control units
NEMA degree of protection	NEMA 1 painted sheet steel with external reset
Auxiliary contact composition	Without
Motor power hp	3 hp 230 V AC 3 phases 3 hp 200 V AC 3 phases
Poles description	3P
System Voltage	600 V AC
NEMA size	0
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Local signalling	No indicator
Motor starter type	Non reversing
Thermal overload type	Melting alloy
Number of thermal units required	3
Disconnecter device type	Fusible disconnect switch R 30 A

### Ordering and shipping details

Category	21212 - 8538,39SB(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901020691
Nbr. of units in pkg.	1
Package weight(Lbs)	35.38000000000003
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------