

A9XPH212

Acti 9 - comb busbar cut - 2P - type N+1L - 18 mm pitch - 12 modules - 100A

Product availability : Stock - Normally stocked in distribution facility



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	1P + N
Number of ways	6 ways, type : N + 1 L (tooth) with 18 mm pitch
Distance between way	1.42 in (36 mm)
Marking	N L
Total number of 18 mm modules	12

Complementary

Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	100 A (40 °C)
System Voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	24
Width	8.66 in (220 mm)
Colour	White (RAL 9003)
Range compatibility	Acti 9 / Acti 9 iC60 Acti 9 / Acti 9 iK60 Acti 9 / Acti 9 iLD Acti 9 / Acti 9 iLD K Acti 9 / Acti 9 iSW Acti 9 / Acti 9 iSW-NA Multi 9 / Multi 9 C60 / C60H Multi 9 / Multi 9 C60 / C60N

Environment

Standards	IEC 61439-2 IEC 60947-7-1
Fire resistance	1760 °F (960 °C) (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7-1

Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901953142
Nbr. of units in pkg.	1
Package weight(Lbs)	0.17000000000000001
Returnability	Y
Country of origin	DE

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------