Product data sheet Characteristics

HOM2448M125PC **HOM INDR 125A MB 24/48CIR**

Product availability: Stock - Normally stocked in distribution facility





Price*: 710.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	125 A	
Number of spaces	24	
Number of circuits	48	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment	Circuit breaker [Space(1) 2P 125 A 120/240 V AC main supply ready assembled	

Complementary

Main		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	125 A	
Number of spaces	24	
Number of circuits	48	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment	Circuit breaker [Space(1) 2P 125 A 120/240 V AC main supply ready assembled	
Complementary Short-circuit current	22 kA	
Number of tandem circuit breakers	24	
Number of tandem circuit breakers Phase	24 1 phase	
Number of tandem circuit breakers Phase System Voltage	24	
Number of tandem circuit breakers Phase System Voltage AWG gauge	24 1 phase 120/240 V AC AWG 6AWG 2/0 aluminium	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration	24 1 phase 120/240 V AC AWG 6AWG 2/0 aluminium AWG 6AWG 1/0 copper	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration	24 1 phase 120/240 V AC AWG 6AWG 2/0 aluminium AWG 6AWG 1/0 copper 3-wire	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material	24 1 phase 120/240 V AC AWG 6AWG 2/0 aluminium AWG 6AWG 1/0 copper 3-wire Tin plated aluminium busbar	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material Enclosure material	24 1 phase 120/240 V AC AWG 6AWG 2/0 aluminium AWG 6AWG 1/0 copper 3-wire Tin plated aluminium busbar Welded sheet steel	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Material Enclosure material Cover finish	24 1 phase 120/240 V AC AWG 6AWG 2/0 aluminium AWG 6AWG 1/0 copper 3-wire Tin plated aluminium busbar Welded sheet steel Gray baked enamel	

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901977155
Nbr. of units in pkg.	1
Package weight(Lbs)	25.1999999999999
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	