Product data sheet Characteristics

HOM4080L225PC HOM INDR 225A MLO 40/80CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 618.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	225 A	
Number of spaces	40	
Number of circuits	80	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	

Complementary

3		
Main		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	225 A	
Number of spaces	40	
Number of circuits	80	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Complementary		
Short-circuit current	10 kA	
Number of tandem circuit breakers	40	
Phase	1 phase	
System Voltage	120/240 V AC	
AWG gauge	AWG 4250 kcmil copper	
	AWG 4300 kcmil aluminium	
Wiring configuration	3-wire	
Material	Tin plated aluminium busbar	
Enclosure material	Welded sheet steel	
Cover finish	Gray baked enamel	
Box number	12	
Environment		
Product certifications	UL E-6294	
-		
And 25, 2047		

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901978145
Nbr. of units in pkg.	1
Package weight(Lbs)	36
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	