Product data sheet Characteristics

HOM4080M200PC HOM INDR 200A MB 40/80CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 1019.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	200 A	
Number of spaces	40	
Number of circuits	80	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled		

Complementary

Main		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	200 A	
Number of spaces	40	
Number of circuits	80	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment	Circuit breaker [Space(1) 2P 200 A 120/240 V AC main supply ready assembled	
Complementary Short-circuit current Number of tandem circuit breakers	22 kA 40	
Phase	1 phase	
System Voltage	120/240 V AC	
AWG gauge	AWG 4250 kcmil aluminium/copper	
Wiring configuration	3-wire	
Material	Tin plated aluminium busbar	
Enclosure material	Welded sheet steel	
Cover finish	Gray baked enamel	
Box number	12	
Environment		
Product certifications	UL E-6294	
Apr 05 2047		

Environment

D 1 4 45 4	=	
Product certifications	UL F-6294	
i roddol ocrimodions	OL L 020-	

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901977575
Nbr. of units in pkg.	1
Package weight(Lbs)	37.67000000000002
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	