

Product availability : Stock - Normally stocked in distribution facility



### Main

Product or component type	Circuit breaker
Range of product	PowerPact L
Trip unit technology	Electronic ammeter Micrologic 5.3 A LSI
Breaking capacity code	J

### Complementary

Protection technology	Current limiter
Line Rated Current	600 A
Poles description	3P
Breaking capacity	65 kA at 480 V AC 25 kA at 600 V AC 100 kA at 240 V AC
System Voltage	600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 2...500 kcmil (aluminium) 1 AWG 2...600 kcmil (copper) 1
Terminal identifier	AL400L61K3
Height	13.39 in
Width	5.5 in
Depth	6.61 in

### Environment

Product certifications	CCC CE CSA UL listed
------------------------	-------------------------------

## Ordering and shipping details

Category	01116 - L ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
GTIN	00785901637790
Nbr. of units in pkg.	1
Package weight(Lbs)	17
Returnability	N
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available