



## Main

Range	Multi 9
Product or component type	Add-on residual current devices
Device short name	Vigi C60
Range compatibility	Multi 9 C60H Multi 9 C60N Multi 9 C60CTRL Multi 9 C60L
Poles description	2P
[In] rated current	63 A conforming to EN/IEC 61009-1
Network type	AC
Network frequency	50/60 Hz
System Voltage	230/400 V AC 50/60 Hz 240/415 V AC 50/60 Hz
Earth-leakage sensitivity	30 mA EN/IEC 61009-1
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class AC
9 mm pitches	4

## Complementary

Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	500 V AC 50 Hz conforming to EN/IEC 61009-1
[Uimp] rated impulse withstand voltage	4 kV conforming to EN/IEC 61009-1
Local signalling	Fault indication
Mounting mode	Clip-on
Mounting support	DIN rail
Electrical connection to mcb	By screws
Height	3.43 in (87 mm)
Width	1.42 in (36 mm)

Depth	2.91 in (74 mm)
Product weight	0.33 lb(US) (0.15 kg)
Colour	Grey
Connections - terminals	Tunnel type terminal, bottom rigid wire(s) 0...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) max Tunnel type terminal, bottom flexible wire(s) 0...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) max Tunnel type terminal, bottom flexible with ferrule wire(s) 0...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) max
Wire stripping length	0.55 in (14 mm) (bottom)
Tightening torque	30.97 lbf.in (3.5 N.m) (bottom)

## Environment

Standards	EN/IEC 61009-1 EN/IEC 61009-2-1
IP degree of protection	IP40 modular enclosure conforming to IEC 60529 IP20 conforming to IEC 60529
Pollution degree	3 conforming to IEC 61009
Electromagnetic compatibility	8/20 µs impulse withstand 250 A conforming to EN/IEC 61009-1
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Ambient air temperature for storage	-40...140 °F (-40...60 °C)

## Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901126829
Nbr. of units in pkg.	1
Package weight(Lbs)	5.0000000000000003E-2
Returnability	N
Country of origin	FR

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0932 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------