Product data sheet Characteristics

QON330L200I OEM BASE ML 240V 120A 3PH 30SP W/ **NETURAL**

Product availability: Stock - Normally stocked in distribution facility



Main

Circuit breaker type	QO
Range of product	QO

Complementary

Main	00	
Circuit breaker type	QO	
Range of product	QO	
Complementary		
[In] rated current	200 A	
System Voltage	208Y/120 V AC	
	240 V AC	
AWG gauge	AWG 4300 kcmil aluminium/copper cable	
Material	Tin plated copper busbar	
Network number of phases	3 phases	
Number of spaces	30	
Short-circuit protection	10 kA	
Product destination	QO circuit breaker	
	QO-GFI circuit breaker	
	QO-EPD circuit breaker	
Wiring configuration	4-wire	
Environment		
Product certifications	UL listed	
	CSA	
0 1 1 1 1 1 1 1 1 1		
Ordering and shipping details Category	S 00909 - MOUNTING BASES, S/N	
Discount Schedule	DE3A	
GTIN	00785901324911	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.740000000000002	

Environment

Product certifications	UL listed	
	CSA	

Ordering and shipping details

Category	00909 - MOUNTING BASES, S/N	
Discount Schedule	DE3A	
GTIN	00785901324911	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.740000000000002	

Returnability	Y
Country of origin	US

Contractual warranty

Warranty period	18 months