



### Main

Commercial Status	Commercialised
Product or component type	Meter Mains
Range of product	Homeline
[In] rated current	200 A
Meter socket type	Ringed
Service feed location	UG OH
Bypass type	No bypass

### Complementary

Short-circuit current	22 kA
Product mounting	Surface
Number of spaces	8
Number of circuits	16
Number of tandem circuit breakers	8
Hub type	A A-L
Electrical connection	Feed-thru lugs service ground Lugs line side
AWG gauge	12...1/0 AWG copper service ground 12...1/0 AWG aluminium service ground 6...300 AWG/kcmil copper line side 6...300 AWG/kcmil aluminium line side
Device composition	Service disconnect (factory installed)
Service disconnect rated current	200 A
Branch circuit breaker rated current	100 A

### Ordering and shipping details

Category	00048 - HOM METER MAINS
Discount Schedule	DE3A
GTIN	00785901859161
Nbr. of units in pkg.	1
Package weight(Lbs)	51.85
Returnability	Y
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.