



### Main

Product or component type	Meter Mains
Range of product	Homeline
Includes	Circuit breaker 1) 2P 200 A 120/240 V AC main supply ready assembled

### Complementary

Line Rated Current	200 A
Short-circuit current	22 kA
Network number of phases	1
Meter socket type	Ringed
Mounting	Surface
Number of spaces	8
Number of circuits	16
Number of Tandem Breakers	8
Hub type	A-L
Electrical connection	Lugs line side Lugs service ground Feed-thru lugs load side
Wire Size	AWG 4...250 kcmil aluminium/copper)line side AWG 6...250 kcmil aluminium/copper)load side AWG 14...AWG 2/0 aluminium/copper)service ground
Tightening torque	Main lugs 250 lb.in, AWG 4...250 kcmil, aluminium/copper Service ground 50 lb.in, AWG 14...AWG 2/0, copper Service ground 50 lb.in, AWG 12...AWG 2/0, aluminium Lugs 250 lb.in, AWG 6...250 kcmil, aluminium/copper Branch lugs 50 lb.in, AWG 14...AWG 2/0, copper Branch lugs 50 lb.in, AWG 12...AWG 2/0, aluminium Cover 10 lb.in
Disconnect	Service disconnect (factory installed)
Main Breaker Rating	200 A
Branch Breaker Rating	110 A
Service feed location	OH UG
Bypass type	No bypass
Maximum Depth	6.30 in (160.02 mm)
Maximum Width	21.50 in (546.10 mm)
Maximum Height	30.26 in (768.60 mm)

### Environment

NEMA degree of protection	NEMA 3R
Product certifications	UL E-6294

## Ordering and shipping details

Category	00148 - HOMELINE CSED DEVICES
Discount Schedule	DE3A
GTIN	00785901340492
Package weight(Lbs)	53.87 lb(US) (24.44 kg)
Returnability	Yes

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>