

STBNCO2212

standard Network Interface Module STB - CANopen bus - 1 Mbit/s

Product availability : Stock - Normally stocked in distribution facility



Main

Range of product	Modicon STB distributed I/O solution
Product or component type	Standard Network Interface Module
Integrated connection type	CANopen bus conforming to CIA DS-301 9-way male SUB-D connector double shielded twisted pair (bus) CANopen bus conforming to CIA DS-301 HE-13 (RS232 port) CANopen bus conforming to CIA DS-301 8-way female (RS232 port)
Number of segments	1 primary, maximum 6 extensions
Number of slave	127
Transmission rate	1 Mbit/s for bus length of 98.43 ft (30 m) 10 kbit/s for bus length of 16404.2 ft (5000 m)
Structure type	CAN field bus

Complementary

Number of addressable I/O module	0...32 per island
Communication service	Network management (NMT) Process Data Object (PDO) Service Data Object (SDO)
[Us] rated supply voltage	24 V DC
Power supply type	SELV
Supply current	>= 700 mA
Supply voltage limits	19.2...30 V
Input current	430 mA for supply circuit
Nominal output current	1.2 A 0.575 A (140...158 °F (60...70 °C))
Output voltage	5.25 V DC (tolerance: +/- 0.21 %) logic bus
Marking	CE
Overvoltage category	II
Status LED	1 LED red module error (ERR) 1 LED green island state (RUN)

	1 LED green power supply (PWR) 1 LED green CAN RUN 1 LED red CAN ERR 1 LED yellow test mode
Depth	2.76 in (70 mm)
Height	1.57 in (40 mm)
Width	5.05 in (128.3 mm)
Product weight	0.3 lb(US) (0.135 kg)

Environment

Electromagnetic compatibility	Immunity to electromagnetic interference conforming to IEC 61131-2
Product certifications	FM Class 1 Division 2 CSA ATEX Cat 3G UL C-Tick
Pollution degree	2 conforming to IEC 60664-1
Operating altitude	<= 6561.68 ft (2000 m)
IP degree of protection	IP20 conforming to EN 61131-2 class 1
Ambient air temperature for operation	32...140 °F (0...60 °C) without derating -13...158 °F (-25...70 °C) with derating factor
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % at 140 °F (60 °C) without condensation
Vibration resistance	+/-0.35 mm (f = 10...58 Hz) 5 gn (f = 58...150 Hz) on 35 x 15 mm symmetrical DIN rail 3 gn (f = 58...150 Hz) on 35 x 7.5 mm symmetrical DIN rail
Shock resistance	30 gn 11 ms conforming to IEC 88 reference 2-27

Ordering and shipping details

Category	18215 - ADVANTYS STB I/O
Discount Schedule	PC32
GTIN	00785901277422
Nbr. of units in pkg.	1
Package weight(Lbs)	0.39000000000000001
Returnability	Y
Country of origin	FR

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0836 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------