Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	Magelis XBT GC, GT/GK with control
Product or component type	CANopen bus master module
Product compatibility	XBTGC1100T XBTGC1100U XBTGC2120T XBTGC2120U XBTGC2230T XBTGC2230U
Integrated connection type	CANopen master bus male SUB-D 9, 2 twisted shielded pairs
Bus type	CANopen conformity class: M10, profile: DS 301 V4.02 CANopen conformity class: M10, profile: DR 303-1
Number of channels	64 TPDO 64 RPDO
[Us] rated supply voltage	5 V DC

Complementary

Complementary		
Transmission rate	500 kbit/s, bus length = <= 410.1 ft (125 m)	
	50 kbit/s, bus length = <= 2624.67 ft (800 m)	
	250 kbit/s, bus length = <= 820.21 ft (250 m)	
	20 kbit/s, bus length = <= 3280.84 ft (1000 m)	
	125 kbit/s, bus length = <= 1394.36 ft (425 m)	
	1000 kbit/s, bus length = <= 164.04 ft (50 m)	
	100 kbit/s, bus length = <= 1640.42 ft (500 m)	
Power dissipation in W	2.4 W at 5 V DC	
Number of modules per base controller	1	
Number of slave	<= 16	
Supply	External supply	
Marking	CE	
Status LED	1 LED for RUN	
	1 LED for PWR	
	1 LED for ERR	
Product weight	0.22 lb(US) (0.1 kg)	

Environment

Product certifications	UL	
IP degree of protection	IP20	
Ambient air temperature for operation	32122 °F (050 °C)	
Relative humidity	1090 % without condensation	

Ordering and shipping details

Category	22568 - HMI CONTROLLERS	
Discount Schedule	MC2	
GTIN	00785901914372	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.48	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	JP	

Offer Sustainability

Sustainable offer status	Not Croop Promium product	
Sustainable offer status	Not Green Premium product	
	·	

Contractual warranty

Period	18 months