



Main

Range of product	OsiSense XG
Product or component type	Portable diagnostic terminal
RFID diagnostic terminal name	XGST
Processor name	CPU ARM7

Complementary

RFID frequency	13.56 MHz
Terminal use	Diagnostics on compact stations Read / write operations on tags
[Us] rated supply voltage	5 V DC AC external adaptor 3.7 V DC internal battery
Autonomy	8 h
Memory description	Expandable USB memory stick, up to 2 GB Internal data storage Compact Flash, 2 GB Internal RAM RAM/SDRAM, 256 kB
Display type	OLED colour touchscreen
Display size	54 x 95 mm
Pixel resolution	480 x 272 pixels
Status LED	1 LED charging
Communication port support	USB RS485 non isolated
Marking	CE
Net Weight	0.65 lb(US) (0.295 kg)

Environment

Product certifications	CE
Ambient air temperature for operation	32...113 °F (0...45 °C)
Ambient air temperature for storage	-4...113 °F (-20...45 °C)
Relative humidity	5...95 %
IP degree of protection	IP40

Ordering and shipping details

Category	22491 - SENS,IDENTIFICATION DEVICE (XGK)
Discount Schedule	DS2
GTIN	03389119081436
Nbr. of units in pkg.	1
Package weight(Lbs)	0.85 lb(US) (0.39 kg)
Returnability	No
Country of origin	FR

Packing Units

Package 1 Height	0.530 dm
Package 1 width	0.890 dm
Package 1 Length	1.640 dm

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

RFID Handheld Terminal

