

# XZCP29P11L5

pre-wired connectors XZ - straight female - M12 -  
8 pins - cable PUR 5m

Product availability : Stock - Normally stocked in distribution facility



## Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	Application

## Complementary

Electrical connection	M12, 8 pins straight female connector
Cable connector fixing	Screw-on
Collar material	Stainless steel 316L
Status LED	Without
Cable length	16.4 ft (5 m)
Cable outer diameter	0.2 in (5.2 mm)
Cable composition	8 x 0.25 mm <sup>2</sup>
Wire insulation material	PUR
System Voltage	30 V AC 36 V DC
Line Rated Current	2 A
Contact resistance	<= 5000 μOhm
Insulating resistance	>= 1 GΩ

## Environment

IP degree of protection	IP67
Product certifications	CULus
Ambient air temperature for operation	-31...194 °F (-35...90 °C) (static) 23...194 °F (-5...90 °C) (flexing)
Ambient air temperature for storage	-31...212 °F (-35...100 °C)

Ordering and shipping details

Category	22499 - SENSORS ACCESSORIES
Discount Schedule	DS2
GTIN	00785901591887
Nbr. of units in pkg.	1
Package weight(Lbs)	0.6099999999999999
Returnability	Y
Country of origin	CZ

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>

Contractual warranty

Warranty period	18 months
-----------------	-----------