



## Main

|                                    |                      |
|------------------------------------|----------------------|
| Accessory / separate part category | Cabling accessory    |
| Accessory / separate part type     | Pre-wired connectors |
| Series name                        | General purpose      |

## Complementary

|                          |                                      |
|--------------------------|--------------------------------------|
| Electrical connection    | M12, 4 pins elbowed female connector |
| Cable connector fixing   | Screw-on                             |
| Collar material          | Metal                                |
| Status LED               | Without                              |
| Cable length             | 6.56 ft (2 m)                        |
| Cable outer diameter     | 0.18 in (4.6 mm)                     |
| Cable composition        | 4 x 0.25 mm <sup>2</sup>             |
| Wire insulation material | PVC                                  |
| System Voltage           | 250 V AC<br>300 V DC                 |
| Line Rated Current       | 3 A                                  |
| Contact resistance       | <= 5000 μOhm                         |
| Insulating resistance    | >= 1 GΩ                              |
| Product weight           | 0.2 lb(US) (0.09 kg)                 |

## Environment

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| IP degree of protection               | IP65<br>IP67                        |
| Product certifications                | CULus                               |
| Ambient air temperature for operation | -13...176 °F (-25...80 °C) (static) |
| Ambient air temperature for storage   | -13...176 °F (-25...80 °C)          |

Ordering and shipping details

|                       |                        |
|-----------------------|------------------------|
| Category              | 22483 - MACHINE CABLES |
| Discount Schedule     | DS3                    |
| GTIN                  | 00785901084082         |
| Nbr. of units in pkg. | 1                      |
| Package weight(Lbs)   | 0.17999999999999999    |
| Returnability         | Y                      |
| Country of origin     | DE                     |

Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 1201 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |

Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|